§ 25.257

operating parameters to prevent unacceptable interference.

[70 FR 24725, May 11, 2005]

§ 25.257 Special requirements for operations in the band 29.1-29.25 GHz between NGSO MSS and LMDS.

- (a) Non-geostationary mobile satellite service (NGSO MSS) operators shall be licensed to use the 29.1–29.25 GHz band for Earth-to-space transmissions from feeder link earth station complexes. A "feeder link earth station complex" may include up to three (3) earth station groups, with each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by a NGSO MSS licensees or applicants pursuant to §101.147.
- (b) A maximum of seven (7) feeder link earth station complexes in the contiguous United States, Alaska and Hawaii may be placed into operation, in the largest 100 MSAs, in the band 29.1–29.25 GHz in accordance with § 25.203 and § 101.147 of this chapter.
- (c) One of the NGSO MSS operators licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of eight feeder link earth station complexes that transmit in the 29.1–29.25 GHz band. The other NGSO MSS operator licensed to use the 29.1–29.25 GHz band may specify geographic coordinates for a maximum of two feeder link earth station complexes that transmit in the 29.1–29.25 GHz band.
- (d) Additional NGSO MSS operators may be licensed in this band if the additional NGSO MSS operator shows that its system can share with the existing NGSO MSS systems.
- (e) All NGSO MSS operators shall cooperate fully and make reasonable efforts to identify mutually acceptable locations for feeder link earth station complexes. In this connection, any single NGSO MSS operator shall only identify one feeder link earth station complex protection zone in each category identified in §101.147(c)(2) of this chapter until the other NGSO MSS operator has been given an opportunity to select a location from the same category.

[61 FR 44181, Aug. 28, 1996]

§ 25.258 Sharing between NGSO MSS Feeder links Stations and GSO FSS services in the 29.25-29.5 GHz Bands.

- (a) Operators of NGSO MSS feeder link earth stations and GSO FSS earth stations in the band 29.25 to 29.5 GHz where both services have a co-primary allocation shall cooperate fully in order to coordinate their systems. During the coordination process both service operators shall exchange the necessary technical parameters required for coordination.
- (b) Licensed GSO FSS systems shall, to the maximum extent possible, operate with frequency/polarization selections, in the vicinity of operational or planned NGSO MSS feeder link earth station complexes, that will minimize instances of unacceptable interference to the GSO FSS space stations. Earth station licensees operating with GSO FSS systems shall be capable of providing earth station locations to support coordination of NGSO MSS feeder link stations under paragraphs (a) and (c) of this section. Operation of ubiquitously deployed GSO FSS earth stations in the 29.25-29.5 GHz frequency band shall conform to the rules contained in §25.138.
- (c) Applicants for authority to use the 29.25–29.5 GHz band for NGSO MSS feeder uplinks will have to demonstrate that their systems can share with GSO FSS and NGSO MSS systems that have been authorized for operation in that band.

[67 FR 37336, May 29, 2002, as amended at 68 FR 16967, Apr. 8, 2003]

§ 25.259 Time sharing between NOAA meteorological satellite systems and non-voice, non-geostationary satellite systems in the 137-138 MHz band.

(a) A non-voice, non-geostationary mobile-satellite service system licensee ("NVNG licensee") time-sharing spectrum in the 137–138 MHz frequency band shall not transmit signals into the "protection areas" of National Oceanic and Atmospheric Administration ("NOAA") satellite systems. When calculating the protection areas for a NOAA satellite in the 137.333–137.367 MHz, 137.485–137.515 MHz, 137.605–137.635 MHz and 137.753–137.787 MHz bands, a